

Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY



Safety Data Sheet dated 23/5/2016, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade code and name: F58 GT ACRYFILLER HS DARK GREY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Two-component primer-surfacer for autobody use

Only for professional use.

1.3. Details of the supplier of the safety data sheet

Company:

Industria Chimica Reggiana I.C.R. Spa

Via Gasparini, 7 42124 REGGIO EMILIA Italia

Tel. +39 0522/517803 Fax +39 0522/514384

Competent person responsible for the safety data sheet:

sdsre@icrsprint.it

1.4. Emergency telephone number

Tel. +39 0522-517803

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

⚠ Warning, Flam. Liq. 3, Flammable liquid and vapour.

⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from open flames - No smoking.

P260 Do not breathe vapours or spray.

P271 Use only outdoors or in a well-ventilated area.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 15% - < 20%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-219485493-29	⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.8/3 STOT SE 3 H336 EUH066
>= 3% - <	Xylene	Index number: 601-022-01-6	⚠ 2.6/3 Flam. Liq. 3 H226



Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY

5%		CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<p>⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.1/4/Dermal Acute Tox. 4 H312 ⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.9/2 STOT RE 2 H373 ⚠ 3.10/1 Asp. Tox. 1 H304</p>
>= 1% - < 3%	2-methoxy-1-methylethyl acetate	Index number: 607-195-00-7 CAS: 108-65-6 EC: 203-603-9 REACH No.: 01-2119475791-29	<p>⚠ 2.6/3 Flam. Liq. 3 H226</p>
>= 1% - < 3%	2-butoxyethyl acetate	Index number: 607-038-00-2 CAS: 112-07-2 EC: 203-933-3 REACH No.: 01-2119475112-47	<p>⚠ 3.1/4/Dermal Acute Tox. 4 H312 ⚠ 3.1/4/Inhal Acute Tox. 4 H332</p>
>= 0.25% - < 0.5%	butanone	Index number: 606-002-00-3 CAS: 78-93-3 EC: 201-159-0 REACH No.: 01-2119457290-43	<p>⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.8/3 STOT SE 3 H336 EUH066</p>
>= 0.25% - < 0.5%	ethylbenzene	Index number: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 REACH No.: 01-2119489370-35	<p>⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.9/2 STOT RE 2 H373 ⚠ 3.10/1 Asp. Tox. 1 H304</p>
>= 0.1% - < 0.25%	Solvent naphtha (petroleum), light arom.	Index number: 649-356-00-4 CAS: 64742-95-6 EC: 265-199-0 REACH No.: 01-2119455851-35	<p>⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.8/3 STOT SE 3 H336 ⚠ 4.1/C2 Aquatic Chronic 2 H411 ⚠ 3.10/1 Asp. Tox. 1 H304 EUH066 DECLP (CLP)*</p>

*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

See section 11 for known symptoms and effects.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).



Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY

Treatment:
None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

Do not use water jets. Water may not be effective fire fighting measure, however it can be used to cool closed containers close to flames as to avoid bursting and exploding.

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

See Point 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

n-butyl acetate - CAS: 123-86-4

EU - LTE(8h): 713 mg/m3, 150 ppm - STE(): 200 ppm

ACGIH - LTE(8h): 713 mg/m3, 150 ppm - STE: 200 ppm - Notes: Eye and URT irr

Xylene - CAS: 1330-20-7

Italy - LTE(8h): 221 mg/m3, 50 ppm - STE(): 442 mg/m3, 100 ppm - Notes: Assorbito attraverso la pelle

EU - LTE(8h): 221 mg/m3, 50 ppm - STE: 442 mg/m3, 100 ppm - Notes: Bold-type: Indicative Occupational Exposure

Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

ACGIH - LTE(8h): 100 ppm - STE: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

2-methoxy-1-methylethyl acetate - CAS: 108-65-6



Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY

Italy - LTE(8h): 275 mg/m³, 50 ppm - STE: 550 mg/m³, 100 ppm - Notes: H
EU - LTE(8h): 275 mg/m³, 50 ppm - STE: 550 mg/m³, 100 ppm - Notes: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)

2-butoxyethyl acetate - CAS: 112-07-2
EU - LTE(8h): 133 mg/m³, 20 ppm - STE: 333 mg/m³, 50 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)
ACGIH - LTE(8h): 20 ppm - Notes: A3 - Hemolysis

butanone - CAS: 78-93-3
Italy - LTE(8h): 600 mg/m³, 200 ppm - STE: 900 mg/m³, 300 ppm
EU - LTE(8h): 600 mg/m³, 200 ppm - STE: 900 mg/m³, 300 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)
ACGIH - LTE(8h): 200 ppm - STE: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

ethylbenzene - CAS: 100-41-4
Italy - LTE(8h): 442 mg/m³, 100 ppm - STE(): 884 mg/m³, 200 ppm - Notes: Pelle
EU - LTE(8h): 442 mg/m³, 100 ppm - STE: 884 mg/m³, 200 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)
ACGIH - LTE(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

Solvent naphtha (petroleum), light arom. - CAS: 64742-95-6
EU - LTE(8h): 100 mg/m³, 19 ppm

DNEL Exposure Limit Values

n-butyl acetate - CAS: 123-86-4
Consumer: 102.34 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Professional: 960 mg/m³ - Consumer: 859.7 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Professional: 480 mg/m³ - Consumer: 102.34 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Professional: 480 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Xylene - CAS: 1330-20-7
Worker Professional: 289 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Professional: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Professional: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-methoxy-1-methylethyl acetate - CAS: 108-65-6
Worker Professional: 153.5 mg/kg - Consumer: 54.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Professional: 275 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

2-butoxyethyl acetate - CAS: 112-07-2
Worker Professional: 133 mg/m³ - Consumer: 67 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 27 mg/kg - Exposure: Human Dermal - Frequency: Short Term, systemic effects - Notes: bw/day
Consumer: 4.3 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects - Notes: bw/day
Consumer: 18 mg/kg - Exposure: Human Oral - Frequency: Short Term, systemic effects - Notes: bw/day
Worker Professional: 773 mg/m³ - Consumer: 499 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects
Worker Professional: 333 mg/m³ - Consumer: 166 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects
Worker Professional: 102 mg/kg - Consumer: 36 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects - Notes: bw/day

butanone - CAS: 78-93-3
Worker Professional: 1161 mg/kg - Consumer: 412 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Professional: 600 mg/m³ - Consumer: 106 mg/l - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 31 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

n-butyl acetate - CAS: 123-86-4
Target: STP - Value: 35.6 mg/l
Target: Fresh Water - Value: 0.18 mg/l
Target: Marine water - Value: 0.01 mg/l
Target: Intermittent emissions - Value: 0.36 mg/l
Target: Freshwater sediments - Value: 0.98 mg/kg
Target: Marine water sediments - Value: 0.09 mg/kg



Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY

Target: Soil - Value: 0.09 mg/kg
 Xylene - CAS: 1330-20-7
 Target: STP - Value: 6.58 mg/l
 Target: Marine water - Value: 0.327 mg/l
 Target: Intermittent emissions - Value: 0.327 mg/l
 Target: Freshwater sediments - Value: 12.46 mg/kg
 Target: Marine water sediments - Value: 12.46 mg/kg
 Target: Soil - Value: 2.31 mg/kg
 Target: Fresh Water - Value: 0.327 mg/l
 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
 Target: Intermittent emissions - Value: 100 mg/l
 Target: Freshwater sediments - Value: 3.29 mg/kg
 Target: Marine water sediments - Value: 0.329 mg/kg
 Target: Soil - Value: 0.29 mg/kg
 Target: Fresh Water - Value: 0.635 mg/l
 Target: Marine water - Value: 0.0635 mg/l
 2-butoxyethyl acetate - CAS: 112-07-2
 Target: Purification plant - Value: 90 mg/l
 Target: Fresh Water - Value: 0.304 mg/l
 Target: Marine water - Value: 0.0304 mg/l
 Target: Intermittent emissions - Value: 0.56 mg/l
 Target: Freshwater sediments - Value: 2.03 mg/kg
 Target: Marine water sediments - Value: 0.203 mg/kg
 Target: Soil - Value: 0.68 mg/kg
 Target: Oral - Value: 0.06 g/kg
 butanone - CAS: 78-93-3
 Target: Freshwater sediments - Value: 284.7 mg/kg
 Target: Soil - Value: 22.5 mg/kg
 Target: Oral - Value: 1000 mg/kg
 Target: Fresh Water - Value: 55.8 mg/l
 Target: Intermittent emissions - Value: 55.8 mg/l
 Target: Purification plant - Value: 709 mg/l

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Use protective gloves that provides comprehensive protection, EN374 Class 3 (B-F-I). Permeation time > 30 minutes; 0.4 mm thickness.

Respiratory protection:

Use adequate protective respiratory devices, using Filter "A" (Brown colour) for organic gas and vapors with boiling points over 65°C.

Thermal Hazards:

None

Environmental exposure controls:

Emissions from ventilation systems or from work processes must be check as to ensure compliance to environmental protection legislation. In some cases the addition of vapour scrubbers, filters or other system modification may be necessary in order to reduce emissions to acceptable levels.

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	Liquid, light grey	--	--
Odour:	Typical of solvent	--	--
Odour threshold:	N.D.	--	--
pH:	7		



Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY

Melting point / freezing point:	- 54°C	--	--
Initial boiling point and boiling range:	127°C	--	--
Flash point:	27°C	--	--
Evaporation rate:	N.D.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.D.	--	--
Vapour pressure:	15 hPa	--	--
Vapour density:	4 (air = 1)	--	--
Relative density:	1,6 g/cm ³	--	--
Solubility in water:	Insoluble	--	--
Solubility in oil:	N.D.	--	--
Partition coefficient (n-octanol/ water):		--	--
Auto-ignition temperature:	415°C	--	--
Decomposition temperature:	N.D.	--	--
Viscosity:	> 20,5 mm ² /s (40°C)	--	--
Explosive properties:	N.D.	--	--
Oxidizing properties:	N.D.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under recommended use and storage conditions (see point 7).

10.3. Possibility of hazardous reactions

It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth), and nitrides.

It may catch fire on contact with oxidising mineral acids, powerful oxidising agents, and powerful reducing agents.

10.4. Conditions to avoid

Stable under normal conditions.



Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 6400 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 21.1 mg/l - Duration: 4h

Xylene - CAS: 1330-20-7

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 6350 ppm - Duration: 4h

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 4350 mg/kg

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 35.7 mg/l

Test: LD50 - Route: Oral - Species: Rat = 8500 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/l

2-butoxyethyl acetate - CAS: 112-07-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 2400 mg/kg

Test: LD50 - Route: Oral - Species: Mouse = 3200 mg/kg

Test: LD50 - Route: Skin - Species: Rat = 1580 mg/kg

butanone - CAS: 78-93-3

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Mouse = 40 mg/l

Test: LD50 - Route: Oral - Species: Rat = 2737 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 13 g/kg

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Mouse = 35500 mg/m³

Test: LC50 - Route: Inhalation - Species: Rat = 55000 mg/m³

Test: LD50 - Route: Oral - Species: Rat = 3500 mg/kg

Solvent naphtha (petroleum), light arom. - CAS: 64742-95-6

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 6193 mg/m³

Test: LD50 - Route: Oral - Species: Rat = 3592 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

a) acute toxicity;

b) skin corrosion/irritation;

c) serious eye damage/irritation;

d) respiratory or skin sensitisation;

e) germ cell mutagenicity;

f) carcinogenicity;

g) reproductive toxicity;

h) STOT-single exposure;

i) STOT-repeated exposure;

j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

n-butyl acetate - CAS: 123-86-4

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 44 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 648 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish = 18 mg/l - Duration h: 96

Xylene - CAS: 1330-20-7



Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 1 mg/l - Duration h: 24
Endpoint: EC50 - Species: Algae = 4.36 mg/l - Duration h: 73
Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96
Endpoint: NOEC - Species: Algae = 0.44 mg/l - Duration h: 73
Endpoint: NOEC - Species: Daphnia = 1.57 mg/l - Duration h: 504
Endpoint: NOEC - Species: Fish = 1.3 mg/l - Duration h: 1344

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 96
Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336
Endpoint: NOEC - Species: Daphnia > 100 mg/l - Duration h: 504
Endpoint: NOEC - Species: Algae > 1000 mg/l - Duration h: 96
Endpoint: LC50 - Species: Fish = 100 mg/l - Duration h: 96
Endpoint: LC50 - Species: Daphnia = 408 mg/l - Duration h: 48

butanone - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 3220 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia > 520 mg/l - Duration h: 48

Solvent naphtha (petroleum), light arom. - CAS: 64742-95-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 3.2 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae = 2.9 mg/l - Duration h: 72
Endpoint: LC50 - Species: Fish = 9.2 mg/l
Endpoint: EC50 - Species: Algae = 1 mg/l - Notes: NOEC

12.2. Persistence and degradability

Not persistent and Biodegradable

12.3. Bioaccumulative potential

Not bioaccumulative

12.4. Mobility in soil

Do not mix with waste water, rain or surface water. Floats on water, evaporates from liquid and solid surfaces but a significant amount may penetrate and pollute water table.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The empty containers must be considered special waste materials to take to dump of type 2B. If previously cleansed, they can be admitted in first class dumps.

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information



Limited quantities, not subject to ADR norms for internal packaging of up to 5 litres and maximum packaging of 30kg.

14.1. UN number

ADR-UN Number:	1263
IATA-UN Number:	1263
IMDG-UN Number:	1263

14.2. UN proper shipping name

ADR-Shipping Name:	PAINT
IATA-Shipping Name:	PAINT
IMDG-Shipping Name:	PAINT

14.3. Transport hazard class(es)

ADR-Class:	3
ADR-Label:	3
ADR - Hazard identification number:	30
IATA-Class:	3



Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY

IATA-Label:	3
IMDG-Class:	3
IMDG-Class:	3
14.4. Packing group	
ADR-Packing Group:	III
IATA-Packing group:	III
IMDG-Packing group:	III
14.5. Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
14.6. Special precautions for user	
ADR-Subsidiary risks:	-
ADR-S.P.:	163 367 640E 650
ADR-Tunnel Restriction Code:	3 (D/E)
IATA-Passenger Aircraft:	355
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3 A72 A192
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-MFAG:	310
IMDG-Storage category:	Category A
IMDG-Storage notes:	-
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
N.A.	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

None

Volatile Organic compounds - VOCs =267.10 g/Kg= 427.36 g/l
Volatile CMR substances = 0.00 %
Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %
Organic Carbon - C = 0.17
Dry weight (% wt):73.29

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.
Regulation (EC) nr 648/2004 (detergents).
1999/13/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):
N.A.

15.2. Chemical safety assessment
No

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.
H332 Harmful if inhaled.
H312 Harmful in contact with skin.
H319 Causes serious eye irritation.



Safety Data Sheet

F58 GT ACRYFILLER HS DARK GREY

H335 May cause respiratory irritation.
H315 Causes skin irritation.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
H304 May be fatal if swallowed and enters airways.
H225 Highly flammable liquid and vapour.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

This safety data sheet has been completely updated in compliance to Regulation 2015/830.
This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.
This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
N.A.:	Not available
N.D.:	Not determined.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

